

Protac™

ScuffGuard

Protac™ ScuffGuard is a 6 mil (150µ) monomeric calendared PVC protective laminating film with a scuff -resistant, textured matte finish, coated on one side with a pressure sensitive, solvent acrylic adhesive that is protected by a single-sided, siliconised Kraft release liner.

- RECOMMENDED FOR LAMINATING MOUNTED PRINTS THAT WILL BE PLACED IN MEDIUM TO HIGH-TRAFFIC INDOOR DISPLAY AREAS
- PROVIDES UV PROTECTION FOR INDOOR AND OUTDOOR GRAPHICS (UP TO 3 YEARS)
- IDEAL FOR TRADESHOW GRAPHICS, POP DISPLAYS, MOUSE PADS, COUNTER MATS, EVENT SIGNAGE, FLOOR GRAPHICS, AND OTHER SIGNAGE WHERE A SCUFF -RESISTANT FINISH IS REQUIRED
- CAN BE COMBINED WITH DRYTAC'S FLOORTAC™ PRINT MEDIA TO CREATE A SLIP-RESISTANT INDOOR FLOOR GRAPHIC DURABLE FOR UP TO 6 MONTHS.

*PROTAC SCUFFGUARD IS NOT SUITABLE FOR OUTDOOR FLOOR GRAPHIC APPLICATIONS.

For more information, performance and warranty guide lines please contact your local Drytac office.

© 2020 Drytac Corporation. E&OE.
All other trademarks are the property of their respective owners.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Matte Textured Monomeric Calendared PVC
Adhesive	Solvent Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side White Kraft

PRODUCT CHARACTERISTIC

Film Thickness	6 mil (150µ)
Adhesive Layer	0.8 mil (20µ)
UV Protection	Yes
Outdoor Durability	5 Years*
Slip Rating	R10 (DIN 51130) Low Slip Potential; Dry: 62; Wet: 31 (EN 13036-4)
Fire Rating	Class 0 (BS 476 Part 6 and 7)
Service Temperature Range	-4°F to 203°F (-20°C to 95°C)
Application Temperature	>41°F (5°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

PROCESS SETTINGS

Equipment Type & Temperature	Speed
Roller Laminator Room temperature to 104°F (40°C)	1 ft to 8 ft (0.3m to 2.5m) per minute
Press	Not recommended

DRYTAC®
ADHESIVE SCIENCE

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5401-B Eubank Road,
Sandston,
Virginia, 23150,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

www.drytac.com

THIRD PARTY CERTIFICATION

PRODUCT NAME:	Protac [™] Scuffguard [™]
PRODUCT PART NUMBER:	PFT
STANDARD:	DIN 51130:2010
CLASSIFICATION:	R10
ISSUE DATE:	Apr 14
TEST REPORT REFERENCE:	PM-14040281

For more information, performance and warranty guide lines please contact your local Drytac office.

These test results are not transferable and may not be relevant or applicable to real life applications. Therefore, Drytac[®] strongly recommends and other regulatory entities may require additional testing to determine the suitability for any specific end application. Refer to Drytac[®] Terms and Conditions of Sale at www.drytac.com for additional liability limitations. This certificate is the property of Drytac[®] Corporation. This certificate and all copies should be returned to Drytac[®] upon request.

DRYTAC[®]

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013

FIRE RATING - THIRD PARTY CERTIFICATION

PRODUCT NAME:	Protac [™] Scuffguard [™]
PRODUCT PART NUMBER:	PFT
STANDARD:	BS 476 Part 6 and 7
CLASSIFICATION:	Class 0
ISSUE DATE:	May 2013
TEST REPORT REFERENCE:	328707

For more information, performance and warranty guide lines please contact your local Drytac office.

These test results are not transferable and may not be relevant or applicable to real life applications. Therefore, Drytac[®] strongly recommends and other regulatory entities may require additional testing to determine the suitability for any specific end application. Refer to Drytac[®] Terms and Conditions of Sale at www.drytac.com for additional liability limitations. This certificate is the property of Drytac[®] Corporation. This certificate and all copies should be returned to Drytac[®] upon request.

DRYTAC[®]

Europe

Filwood Road,
Fishponds,
Bristol, BS16 3RY,
United Kingdom
bristol@drytac.com
Tel: +44 (0) 117 958 6500

Canada

30 Driver Road,
Brampton,
Ontario, L6T 5V2,
Canada
toronto@drytac.com
Tel: +1 800.353.2883

USA

5601 Eastport Boulevard,
Richmond,
Virginia, 23231,
USA
customerservice@drytac.com
Tel: +1 800.280.6013